



# ULiQ for Surge Protective Devices



Surge Protective Devices

E326289

Guide Information

## Citel America Inc

10108 USA Today Way, Miramar FL 33025

**Cat No(s): DS42-280%**

| <u>SPD Type</u> | <u>Volts (V)</u> | <u>AC/DC DC PV</u> | <u>Phase</u> | <u>Amps (A)</u> | <u>Ambient Min(°C)</u> | <u>Ambient Max(°C)</u> | <u>Mode</u> | <u>VPR (Vpk)</u> | <u>MLV (Vpk)</u> | <u>MCOV (V)</u> | <u>Vn (Vdc)</u> | <u>In (kA)</u> | <u>SCCR (kA)</u> | <u>Notes</u> |
|-----------------|------------------|--------------------|--------------|-----------------|------------------------|------------------------|-------------|------------------|------------------|-----------------|-----------------|----------------|------------------|--------------|
| 4CA (5)         | 400/230          | AC                 | 3Y           | N/A             | -35                    | 60                     | L-L         | -                | 2730             | 480             | -               | 20             | N/A              | 2            |
|                 |                  |                    |              |                 |                        |                        | L-G         | -                | 1600             | 275             | N/A             |                |                  |              |
| 4CA (5)         | 400/230          | AC                 | 3Y           | N/A             | -35                    | 60                     | L-L         | -                | 2730             | 480             | -               | 10             | N/A              | 2            |
|                 |                  |                    |              |                 |                        |                        | L-G         | -                | 1600             | 275             | N/A             |                |                  |              |

Evaluated to: UL 1449 4th Ed. Rev: 2016-03-17 and CSA Electrical Certification Notice 516/CSA C22.2 No. 8 13

% - May be followed by S

- - L-L modes may also be labeled as L-N modes

Note 2 - Suitable for Field and Factory wiring.

Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report

Date: 2010-02-25

Last 2016-04-18

Revised:

© 2018 UL LLC

