



# ULiQ for Surge Protective Devices



Surge Protective Devices

E326289

Guide Information

## Citel America Inc

10108 USA Today Way, Miramar FL 33025

### Cat No(s): DS215-400

| <u>SPD</u><br><u>Type</u> | <u>Volts</u><br><u>(V)</u> | <u>AC/DC</u><br><u>DC PV</u> | <u>Phase</u> | <u>Amps</u><br><u>(A)</u> | <u>Ambient</u><br><u>Min(°C)</u> | <u>Ambient</u><br><u>Max(°C)</u> | <u>Mode</u> | <u>VPR</u><br><u>(Vpk)</u> | <u>MLV</u><br><u>(Vpk)</u> | <u>MCOV</u><br><u>(V)</u> | <u>Vn</u><br><u>(Vdc)</u> | <u>In</u><br><u>(kA)</u> | <u>SCCR</u><br><u>(kA)</u> | <u>Notes</u> |
|---------------------------|----------------------------|------------------------------|--------------|---------------------------|----------------------------------|----------------------------------|-------------|----------------------------|----------------------------|---------------------------|---------------------------|--------------------------|----------------------------|--------------|
| 4CA (5)                   | 400/230                    | AC                           | 3Y           | n/a                       | -35                              | 60                               | L-L         | -                          | 2350                       | 600                       | n/a                       | 5                        | n/a                        | 1            |
|                           |                            |                              |              |                           |                                  |                                  | L-G         | -                          | 1330                       | 400                       | n/a                       |                          |                            |              |

Evaluated to: UL 1449 4th Ed. Rev: 2016-03-17 and CSA Electrical Certification Notice 516/CSA C22.2 No. 8 13

- - L-L modes may also be labeled as L-N modes

Note 1 - Suitable for Factory wiring only.

Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report

Date: 2012-05-12

Last 2016-03-29

Revised:

© 2018 UL LLC

